



Product specification

Double Insulated Cable

LSZH Insulated and Sheathed Cable



Description

Flexible single core cabling generally used for DC power supplies in the telecoms industry and other power supply applications where a flexible cable is required. The LSZH construction makes the cable particularly suited to installation where, when subjected to fire, the emission of smoke and toxic gases may pose a threat to life.

Specification

Electrical Specifications		
Voltage Grade	450/750v to 35sqmm	
Temperature Range	0°C to +90°C	
Minimum Bending Radius	4 x OD	
Approvals/Standards	Gen. to BS7211 (to 35sqmm) IEC60502-1 (50sqmm+)	
Size mm ²	Approx. OD mm	Weight Kg/km
4	5.7	59
6	6.8	80
10	7.1	120
16	8.4	175
25	10.2	265
35	11.6	365

The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informative purposes only and are subject to change

Hughes Electronics Ltd
Unit G, Southwark Business Center,
Ayres Street, London, SE1 1ES, UK
Co. No. 2827242 VAT No. 653 5771 17

Tel: (44) 020 7378 1400
Fax: (44) 020 7378 1434
email: sales@hugheselectronics.co.uk
web: www.hugheselectronics.co.uk



Making Good Ideas Happen