



# Product specification

## Outdoor DC Breakout Box for 4 RRU

### 35-HEBB04



\*Pictures for illustrative purposes only (4 way version presented)

## Description

Pre-assembled outdoor DC Power breakout enclosure with hinged lid designed to provide power for up to 4x40A to 4 RRUs.

## Specification

Input type	M32x1.5mm cable gland For 2 core cables up to <b>25mm<sup>2</sup></b> shielded power cable. Cable diameter <b>14 – 25mm.</b>
Input rated current	<b>160A</b>
Internal Connections	10mm <sup>2</sup> blue and grey power cable
Output connections	4 x Harting HAN-Modular ECO <b>IP65</b>
Output rated current	<b>4 x 40A</b>
Output Cable Connection	Up to <b>4 x 2-way</b> Harting HAN-Modular ECO <b>IP65</b> power connectors with 6mm <sup>2</sup> 2 core shielded power cable
Earth connection	Preassembled 10mm <sup>2</sup> earth wire with M8 crimp terminal
Enclosure type	<b>IP68</b> plastic enclosure with hinged lid and mounting brackets
Enclosure material	UV protected Polycarbonate, flame retardant
Enclosure size	182mm x 180mm x 90mm excluding mounting brackets & connectors
Operating temperature	-40 °C to +80 °C
Weight	1.4kg
Rohs	Compliant
Additional features	Pressure Compensation Element for IP6x enclosures; Optional surge arrestor; 2 and 3 RRU versions available on request

The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

**Hughes Electronics Ltd**  
Unit G, Southwark Business Center,  
Ayes Street, London, SE1 1ES, UK  
Co. No. 2827242 VAT No. 653 5771 17

Tel: (44) 020 7378 1400  
Fax: (44) 020 7378 1434  
email: sales@hugheselectronics.co.uk  
web: www.hugheselectronics.co.uk



*Making Good Ideas Happen*