




Product Specification

N TYPE FEMALE TO 4.3-10 MALE ADAPTOR

01-6326C110



Description

N Type Female to 4.3-10 Male Adapter LOW PIM

Material and Plating

Centre Contact	Tin Bronze/Sliver Plated
Outer Contact & Body	Brass/Sliver Plated
Dielectric	PTFE
Gasket	Silicon Rubber
Nut	Brass/Nickel Plated

Electrical Characteristics

Characteristics Impedance	50 Ohm	
Frequency Range	DC~6.0GHz	
Insulation Resistance	≥10,000MΩ	
Contract Resistance	NF	4.3-10M
	Centre Contact	≤1.0mΩ ≤1.5mΩ
	Outer Contact	≤0.25mΩ ≤1.5.mΩ
Dielectric Withstanding Voltage	2500V rms	
Working Voltage	1400V rms	
Insertion Loss	@DC-3GHz	≤0.10dB
	VSWR	@DC-3GHz ≤1.10
PIM3 (2*43dBm)	≤-160dBc	

Environmental and Mechanical Specifications

Durability (matings)	≥500 cycles
Thermal Shock Test Method	MIL-STD-202, Method 213G, Test Condition D
Vibration Test Method	MIL-STD-202, Method 204, Test Condition A
Temperature Range	-65 to +165°C
RoHS	Compliant
ISO 9001@2015	Compliant

Hughes Electronics Ltd
 Unit G, Southwark Business Center,
 Ayres Street, London, SE1 1ES, UK
 Co. No. 2827242 VAT No. 653 5771 17

Tel: (44) 020 7378 1400
 Fax: (44) 020 7378 1434
 email: sales@hugheselectronics.co.uk
 web: www.hugheselectronics.co.uk



Making Good Ideas Happen