



Material & Finishing

- 1.Center conductor : Phosphor Bronze,Gold Plating
- 2.Insulators : PTFE
- 3.Body: Brass,Ternary alloy Plating
- 4.Other: Brass,Nickel Plating
- 5.Gasket: Silicone Rubber

Electrical Data

- 1.Characteristic Impedance: 50 Ohms
- 2.Frequency: 0~6GHz
- 3.VSWR: 1.25(DC-4GHz)
- 4.Dielectric Resistance: $\geq 5000M\Omega$

UNLESS OTHERWISE NOTED
ALL SURFACES FINISHED TO $\nabla 6.4$ MAX.

ALL TOLERANCES ARE:

DECIMALS	CHAMFER	ANGLES
0~6 \pm 0.08	0.5~3 \pm 0.5	0~10 \pm 1°
6~30 \pm 0.1	3~6 \pm 0.5	10~50 \pm 30'
30~120 \pm 0.2	6~30 \pm 1	50~120 \pm 20'



Unit G, Southwark Business Centre
Ayres Street, London, SE1 1ES, UK
Tel: (44) 0207 378 1400
Fax (44) 020 7378 1434
www.hugheselectronics.co.uk

Title: N-Type Right Angle Male to SMA Female Adaptor

Part no: 01-65266112

Date: 03/12/2021 **Issue No.** 1 **Scale:** No

Changes log:

Drawn: J. S. _____
 Approved: J. W. _____
 Checked: L. V. _____
 QA: G. R. _____

Compliance:

