



Product specification

HUGHES 7/8" LLCF FEEDER CABLE

19-RF3111404



Description

High performance 7/8" coaxial cable to be used in RF systems. Low PIM and VSWR leads to higher energy efficiency and lower outer interference. Wide range of applications.

Specification

Construction Materials	
Inner Conductor	Smooth copper tube
Dielectric	Physical Foam Polyethylene
Outer Conductor	Corrugated Copper Tube
Jacket	Low Smoke Halogen-free Fire-retardant
CPR Class	B2ca s1a d0 a1
Physical Dimensions	
Inner Conductor Diameter	8.85 ± 0.1mm
Dielectric Diameter	22.80 ± 0.4mm
Outer Conductor Diameter	24.90 ± 0.4mm
Diameter Over Jacket	27.50 ± 0.5mm
Weight	0.39 kg/m
Mechanical Specifications	
Minimum Bending Radius	
Single Bending	90mm
Repeated Bending	250mm
Minimum Number of Bends	15
Tensile Strength	1300N
Electrical Specifications	
Capacitance	75.0pF/m
Impedance	50 ± 2Ω
Velocity	89%

The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Hughes Electronics Ltd
Unit G, Southwark Business Center,
Ayres Street, London, SE1 1ES, UK
Co. No. 2827242 VAT No. 653 5771 17

Tel: (44) 020 7378 1400
Fax: (44) 020 7378 1434
email: sales@hugheselectronics.co.uk
web: www.hugheselectronics.co.uk



Making Good Ideas Happen



Product specification

HUGHES 7/8" LLCF FEEDER CABLE

19-RF3111404

RF Peak Voltage		3.00 kV	
Peak Power Rating		91 KW	
Cut-off Frequency		5.2GHz	
Shielding Effectiveness > 10MHz		>120dB	
Insulation Resistance		5000MΩ•km	
VSWR			
0.8-1.0GHz		≤1.20	
1.7-2.2GHz		≤1.20	
2.2-2.7GHz		≤1.20	
3.3-3.8GHz		≤1.20	
Performance			
Frequency	Attenuation (dB/100m)	Attenuation (dB/100ft)	Average Power Rating (kW)
100	1.19	0.36	8.62
150	1.47	0.45	7.20
200	1.71	0.52	5.99
280	2.05	0.62	4.94
450	2.64	0.80	3.88
800	3.62	1.10	2.83
900	3.87	1.18	2.65
1000	4.10	1.25	2.50
1500	5.16	1.57	1.99
1800	5.73	1.75	1.79
2000	6.09	1.86	1.68
2200	6.44	1.96	1.59
2400	6.78	2.07	1.54
2500	6.95	2.12	1.50
2600	7.12	2.17	1.46
2700	7.29	2.22	1.43
3000	7.74	2.36	1.33
3300	8.25	2.51	1.26
3400	8.42	2.57	1.23
3500	8.58	2.62	1.20
3600	8.74	2.66	1.17
3800	9.05	2.76	1.14
Enviromental Specifications			
Storage Temperature		-40~+70℃	
Installation Temperature		-20~60℃	
Operation Temperature		-40~+70℃	

The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Hughes Electronics Ltd
Unit G, Southwark Business Center,
Ayres Street, London, SE1 1ES, UK
Co. No. 2827242 VAT No. 653 5771 17

Tel: (44) 020 7378 1400
Fax: (44) 020 7378 1434
email: sales@hugheselectronics.co.uk
web: www.hugheselectronics.co.uk



Making Good Ideas Happen