



Product specification

HUGHES VISUAL FAULT LOCATOR



Description

Handheld 650nm visual fault locator with pulsed and CW modes, rugged waterproof design, and up to 30mW output for fibre break detection up to 10km.

Specification

Part NO.	BML-205-1	BML-205-10	BML-205-15	BML-205-20	BML-205-25	BML-205-30
Output Power	> 1mW	> 10mW	> 15mW	> 20mW	> 25mW	> 30mW
Dynamic Distance	3~5 km	8~10 km	> 10km	> 10km	> 10km	> 10km
Wavelength	650nm 20nm					
Operation Mode	Pulsed(2Hz) and CW					
Connector	2.5mm UPC(or custo mize 1.25mm UPC)					
Size(H*W*D)	175mm * 26mm * 26mm					
Weight	80g					

The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Hughes Electronics Ltd
Unit G, Southwark Business Center,
Ayes Street, London, SE1 1ES, UK
Co. No. 2827242 VAT No. 653 5771 17

Tel: (44) 020 7378 1400
Fax: (44) 020 7378 1434
email: sales@hugheselectronics.co.uk
web: www.hugheselectronics.co.uk



Making Good Ideas Happen