



Product specification

MPO-LC Jumpers

MPO-FLX LC



Description

Hughes MPO/APC to 3x FLX DLC singlemode G657A2 jumpers. Compact, low-loss solution for dense fibre distribution.

Specification

Connector Specifications	
Connector Type A	MPO/APC/F/SM/6C
Standard Loss	≤0.75dB
Elite Loss	≤0.35dB
Return Loss	≥60dB
Connector type B	FLX/DLC
Elite Loss	≤0.3dB
Return Loss	≥50dB
Tesr Wavelength	@1310/1550nm
Repeatability	≤0.2dB
Interchangeability	≤0.2dB
Durability	800~1000
Operating Temperature	-40~75°C
Cable Specifications	
Fibre Type	SM/G657A2
Fibre Count	6C
Sub-unit Dimension	3.0mm
Sub-unit Material	PVC
Sub-unit Colour	White
Outer Jacket Dimension	5.0mm
Outer Jacket Material	LSZH
Outer Jacket Colour	Black

The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Hughes Electronics Ltd
Unit G, Southwark Business Center,
Ayles Street, London, SE1 1ES, UK
Co. No. 2827242 VAT No. 653 5771 17

Tel: (44) 020 7378 1400
Fax: (44) 020 7378 1434
email: sales@hugheselectronics.co.uk
web: www.hugheselectronics.co.uk



Making Good Ideas Happen